

All-in-One: Panel PC Systems



Model / Type

Size

CPU

Chipset

Resolution

Display colours

Brightness

Contrast ratio

I/O Ports

Power consumption

Size / Weight

MTBF backlight

Misc.

Options

Availability

Small Screen AIO Fanless Series

7-12"

7" / 8.4" / 10.4" / 12.1"

AMD Geode™ LX800

AMD Geode™ LX800 + AMD Geode™ CS5536

7"	800 × 480
8.4"	800 × 600
10.4"	800 × 600
12.1"	1024 × 768

16.7 M (8 bit for R,G,B)

450 cd/m<sup>2</sup>

500:1 typ.

2× USB, 2× LAN, 1× RS-232

7" / 8.4"	20 W max.
10.4"	25 W max.
12.1"	29 W max.

7"	226 × 140 × 41 mm / 0.6 kg
8.4"	234 × 184 × 42 mm / 0.8 kg
10.4"	276 × 227 × 50.7 mm / 1.4 kg
12.1"	304 × 246 × 50 mm / 1.8 kg

50,000 h

Included - touch screen, wireless NIC, 1 GB RAM, integrated audio;

12.1" storage via HDD or CF

7", 8.4" 10.4" storage via CF

OS - XPE on CF, XP PRO on HDD

CF Type II, SSD via CF, Bluetooth,

mounts - stand, wall, arm, card reader

Worldwide

Small Screen Intel® Fanless Series

15-19"

15" / 17" / 19"

Intel® Celeron® M1.0

Intel® 915GME / 910 GMLE

15"	1024 × 768 max.
17"	1280 × 1024 max.
19"	1280 × 1024 max.

16.7 M (8 bit for R,G,B)

300 cd/m<sup>2</sup>

700:1 typ.

4×USB, 2× LAN, 1× RS-232, 1× RS-232 / 422 / 485

15"	41 W max.
17"	61 W max.
19"	68 W max.

15"	394 × 309 × 61 mm / 3.2 kg
17"	428 × 350 × 65 mm / 5 kg
19"	470 × 383 × 67 mm / 5.8 kg

50,000 h

Included - touch screen, wireless NIC, 1 GB RAM, integrated audio; storage via 2.5" SATA HDD loaded with Win XP Pro

Bluetooth, card reader, wall mount

Worldwide